

LW 100 E1 ECO



The LW 100 ECO compressors are lightweight, reliable and ideal for mobile use. They are made of 100% proven elements from our successful LW 100 series. The main components such as e.g. Motor, compressor block, filter system and filling device are used completely from this series. The steel piston rings in the compressor stages provide long term consistent delivery performance (fill time).

Specifications

- » Electro motor (E-Motor / 230V / 1 Phase / 50Hz)
- » Power cable with plug
- » Start/Stop Switch
- » Aluminium frame
- » Manual condensate drain
- » Pressure maintaining and non return valve
- » 1x Filling hose c/w filling valve and pressure gauge
- » Intermediate coolers
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after for each stage
- » Pistons c/w steel piston rings
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- » Carrying handles
- » Filling valve holder
- » Additional filling hose c/w filling valve
- » Automatic condensate drain
- » Automatic stop at final pressure c/w hour counter
- » Switch over device for 200 or 300 bar
- » Motor protection switch
- » Special voltages / frequencies on request
- » Conversion set: Petrol-/electro version

Difference to the Standard-Model

- » Frame in a aluminium (Standard: s/s)
- » No carrying handles
- » Unpainted compressor block
- » No filling valve holder



Technical Data

LW 100 E1 ECO	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm ³ /h] / [cfm]:	100 / 6 / 3.5
Max. Pressure [bar]:	330
RPM [1/min]:	2300
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 230V / 1 Phase / 50Hz
Drive power [kW] with 50 Hz / 60 Hz:	2.2 / 2.2
Cooling air req. [m ³ /h] with 50 Hz / 60 Hz:	660 / 660
Lubrication type:	Splash oil
Oil capacity [litre]:	0.5
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m ³ at +20°C] ¹⁾ :	108 (at +20°C / approx. 18 h)
Dimensions W x D x H [mm]:	670 x 400 x 400
Weight [kg]:	42
Noise level (measured at 1 m) [dB]:	82

¹⁾ In accordance with EN 12021

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0

Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com

Internet: www.lw-compressors.com