

LW 225 E



User-friendly compressor with electric motor and in a compact design. The portable LW 225 E is ideal for mobile applications or occasional filling operations.

Specifications

- » Electro motor (E-Motor / 400V / 3 Phase / 50 Hz)
- » Power cable with plug and phase selector
- » Start/Stop Switch
- » Steel frame c/w carrying handles
- » Manual condensate drain
- » Pressure maintaining and non return valve
- » 1x Filling hose c/w filling valve and pressure gauge
- » Intermediate coolers
- » Stainless steel pipes
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after each stage
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- » Additional filling hose c/w filling valve
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Switch over device for 200 and 300 bar
- » Hour counter
- » Special voltages / frequencies on request
- » Conversion set: Petrol-/electro version



Technical Data

LW 225 E	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm ³ /h] / [cfm]:	225 / 13.5 / 7.9
Max. Pressure [bar]:	330
RPM [1/min]:	1850
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 400V / 3 Phase / 50 Hz
Drive power [kW] with 50 Hz / 60 Hz:	5.5 / 6.6
Cooling air req. [m ³ /h] with 50 Hz / 60 Hz:	1650 / 1980
Lubrication type:	Splash oil
Oil capacity [litre]:	0.8
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m ³ at +20°C] ¹⁾ :	200 (at +20°C / approx. 15 h)
Dimensions W x D x H [mm]:	780 x 450 x 560
Weight [kg]:	92
Noise level (measured at 1 m) [dB]:	87

¹⁾ In accordance with EN 12021

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0
Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com
Internet: www.lw-compressors.com