

Puracon Stationary ECO



The usage of a humidity controller is the most reliable and economic method for filter monitoring. L&W Puracon filter monitoring systems can be ordered optionally for a new unit or can be easily integrated retroactively into existing filling stations.

Puracon Stationary ECO

Puracon Stationary ECO is a cost-efficient solution for humidity monitoring during the filling procedure.

The Puracon Stationary ECO can be connected directly to the high-pressure line after the humidity filter. The humidity value can be observed during the entire filling procedure. Exceeding of the limits will be indicated by a red LED.

- » Adjustable measuring speed
- » Auto shut down (battery saving mode)
- » Pressure compensation
- » Higher accuracy by new temperature compensation
- » Storage of max. humidity value
- » Alarm LED - freely adjustable limit



Technical Data

	Puracon Stationary ECO
Operating pressure	150 to 350 bar - adjustable pressure range
Power supply	2 x AAA LR03 alk. battery
Connector	G1/4 thread
Protection rating	IP64
Operating temperature	-10°C to +40°C
Dimensions	60 x 90 x 40 mm

Lenhardt & Wagner GmbH

An der Tuchbleiche 39

68623 Hüttenfeld/Germany

Phone: +49 (0)62 56 - 8 58 80 -0

Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com

Internet: www.lw-compressors.com